

Monitor. Integrate. Alert. Peace of Mind.

Applications

Many monitoring installations benefit from the use of both our chemical sensing cable and conductive fluid sensing cable.

Use the SR-KIT to join together these two different types of cable in one single run, and then monitor those cables with one leak detection controller.

Key Features

- Leverage different types of leak detection cables in a single run, monitored by one controller.
- The SR-KIT doesn't affect the total quantity of sensing cable that can be connected to a controller.
- Each SR-KIT comes with the adapters you need for any application:
 - SR-OMGF: Orange male connector to green female connector
 - SR-GMOF: Green male connector to orange female connector



Multiple Types Of Cable Monitored By One Controller

If your application includes different types of RLE cables, use the SR-KIT to join them together in a single run, monitored by a single leak detection controller.

What Sets RLE's SR-KIT Apart?

The SR-KIT does not affect the accuracy of system readings or limit the amount of sensing cable that can be connected to a leak detection controller. Use an SR-KIT to:

- **Monitor different types of sensing cables with a single controller.** Use the SR-KIT to connect conductive fluid and chemical sensing cables together in a single run and monitor them with one leak detection controller.
- **Add another type of cable to an existing install.** The SR-KIT lets you add a section of a different type sensing cable to an existing application. If you're monitoring for fluid leaks and want to add a section of chemical cable, the SR-KIT makes that task quick and easy.

Single Run Cable Kit • For use with SC and SC-C.

Product Codes


SR-KIT	3.5" section of RLE's standard non-sensing cable fitted with compatible cable connectors allows users to connect chemical and conductive fluid sensing cable in a single run. Includes two parts: SR-GMOF (chemical sensing cable male connector; conductive fluid sensing cable female connector) and SR-OMGF (conductive fluid sensing cable male connector; chemical sensing cable female connector)
--------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



SR-GMOF



SR-OMGF



SR-KIT connecting chemical and conductive fluid leak detection cables.

Technical Specifications

Sheer Strength	>180 lbs. (>81.65kg)
Cut Through Resistance	>40 lbs. (>18.14kg) with .005in (0.127mm) blade
Abrasion Resistance	60 cycles per UL 719
Connector Plastic Metal	4 pin, 0.96in (24.38mm) diameter 4 pin, 0.51in (13mm) diameter
Operating Environment Temperature Humidity Altitude	32° to 167°F (0° to 75°C) 5% to 95% RH, non-condensing 15,000ft (4,572m) max.
Storage Environment	-22° to 185°F (-30° to 85°C)
Dimensions (per Part)	8.3" (21cm); .07lbs. (32g)
Certifications	CE and ETL when used with RLE leak detection controllers; RoHS Compliant; Plenum Rated

