



Spot Detector Product Matrix

RLE Technologies produces a variety of spot detectors for your leak detection system, each with their own unique features. Our sales and support staff is always available to help you choose the spot detector that's best suited for your application.

www.rletech.com

800.518.1519

104 Racquette Drive, Fort Collins, CO 80524

sales@rletech.com

	SD	SD-Z	SD-Z1	SD-RO1	SD-RO2
Compatibility	FMS	Any SeaHawk controller, WiNG-LD	Any zone leak detection controller, WiNG-LD	Any product that accepts a digital dry contact input	Any product that accepts a digital dry contact input
Leader Cable Length (Non-Sensing)	14 feet (4.27m)	Two, 10 inch (0.25m)	14 feet (4.27m)	14 feet (4.27m)	14 feet (4.27m)
Connector	SD leader cable wires directly into controller	SD leader cable wires directly into controller	SD leader cable wires directly into controller	SD leader cable wires directly into controller	SD leader cable wires directly into controller
Power	Powered by panel	Powered by panel	Powered by panel	Isolated 24VAC/VDC supply	Isolated 24VAC/VDC supply
Relay Output				One relay output	Two relay outputs
Local Audible Alarm					✓
Local Visible Alarm					✓
Sensor Probe Height	Adjustable, from 0" to 0.19" (0mm - 4.8mm)	Adjustable, from 0" to 0.19" (0mm - 4.8mm)	Adjustable, from 0" to 0.19" (0mm - 4.8mm)	Adjustable, from 0" to 0.19" (0mm - 4.8mm)	Adjustable, from 0" to 0.19" (0mm - 4.8mm)
Dimensions	1.55"W x 2.0"H x 1.0"D	1.55"W x 2.0"H x 1.0"D	1.55"W x 2.0"H x 1.0"D	1.55"W x 2.0"H x 1.0"D	1.55"W x 2.0"H x 1.1"D
Weight	4 oz. (105g)	3 oz. (93g)	5 oz. (136g)	7 oz. (192g)	8 oz. (219g)