# RLETRIAD EXPRESSTechnologiesA Quick Turn Program On TRIADSlotted and Chamfer Panels

#### AIRFLOW PANELS, PATENTED FEATURES

SHIPPED DIRECT, WITHOUT THE WAIT

The TRIAD EXPRESS is a program designed with your immediate need in mind, whereby you can place an order for TRIAD floor panels that would ship on an expedited basis.



Triad Slotted Floor Panel in Grey Flek



Triad Chamfer Floor Panel in Crystal White

# **TRIAD EXPRESS PROGRAM DETAILS**

- Order Quantities: 1 to 30 qualifying airflow panels
- Email Orders To: orders@rletech.com
- Shipment Receipt: 1 to 2 weeks after receipt of order
- TRIAD EXPRESS Orders Will Be Entered Within 24 Hours after receipt, and therefore cannot be canceled

### WHY YOUR CUSTOMERS SHOULD CHOOSE RLE TRIAD HIGH AIRFLOW PANELS

- Patented Stratification Fins create turbulent airflow where you need it
- **Patented Integrated Dual Handles** make lifting and moving panels fast, safe, and easy
- Compatible with all new and existing raised floor systems
- Surpass ADA Requirements for aisle width, grate gap; exceeds industry standard for heel-safe grating

## QUESTIONS? CONTACT US AT 800-518-1519

Program Qu	alifying Slotted Panel Product Codes	
Crystal White	Product Description	Grey Flek
15TSS-CWT	Slotted panel; Imperial sized (24" x 24"); 1500 lb load rating; Available in crystal white or grey flek powder coat	15TSS-GFT
15TSM-CWT	Slotted panel; Metric sized (600 mm x 600mm); 1500 lb load rating; Available in crystal white or grey flek powder coat	15TSM-GFT
30TSS-CWT	Slotted panel; Imperial sized (24" x 24"); 3000 lb load rating; Available in crystal white or grey flek powder coat	30TSS-GFT
30TSM-CWT	Slotted panel; Metric sized (600mm x 600mm); 3000 lb load rating; Available in crystal white or grey flek powder coat	30TSM-GFT
Program Qu	alifying Chamfer Panel Product Codes	
Crystal White	Product Description	Grey Flek
15TCF-CWT	Chamfer panel; Imperial sized (24" x 24"); 1500 lb load rating; Available in crystal white or grey flek powder coat	15TCF-GFT

15TCM-CWTChamfer panel; Metric sized (600 mm x 600mm); 1500 lb load rating; Available in crystal white or grey flek powder coat15TCM-GFT30TCF-CWTChamfer panel; Imperial sized (24" x 24"); 3000 lb load rating; Available in crystal white or grey flek powder coat30TCF-GFT30TCM-CWTChamfer panel; Metric sized (600mm x 600mm); 3000 lb load rating; Available in crystal white or grey flek powder coat30TCM-GFT